

# KP80E



## Data Sheet

<b>Backing:</b>	E-Paper
<b>Bonding Agent:</b>	Resin
<b>Grain:</b>	Aluminium oxide
<b>Coating:</b>	Close
<b>Sectors of Application:</b>	Wood / floor, lacquer / paint, leather / shoes, metal
<b>Utilisation:</b>	Wide belt sanders, long belt sander, oscillating sander, edge grinding, manual belt sander
<b>Advantages:</b>	<b>Speciality: Also available with velcro backing in grit range 24 and 36 - 150 or self-adhesive backing in grit range 40 – 600!</b> Particularly suitable for endless abrasive belts.



### Application:

Wood	Metal	Leather	Lacquer	Floor	Glass
✓	✓	✓	✓		



### Available Grain Numbers:

	16		20	✓	24
	30	✓	36	✓	40
✓	50	✓	60	✓	80
✓	100	✓	120	✓	150
✓	180	✓	220	✓	240
✓	280	✓	320	✓	360
✓	400	✓	500	✓	600
✓	800		900		1000
	1200		1500		2000

**Utilisation:** Machine grinding



Manual grinding



**Forms:** Rolls



Belts



Sheets



Discs



**AWUKO ABRASIVES**  
**Wandmacher GmbH & Co. KG**

Hedemündener Straße 9  
D-34346 Hann. Münden

E-Mail: [info@awuko.com](mailto:info@awuko.com)  
Website: <http://www.awuko.com/>

Phone: +49 (0)5541 7097-0  
Fax national: 05541 6727  
Fax international: +49 (0)5541 6729